

ECOSOFT STANDARD PRO REVERSE OSMOSIS FILTER WITH MINERALIZATION AND PUMP





KEY FEATURES:

- 1. Reliable and affordable solution
- 2. 5 stages of water purification including mineralization
- 3. Designed for low pressure water supply systems
- 4. All components fall within the scope of NSF/ANSI 58, which means that materials in the filters are safe

FILTRATION TECHNOLOGY:

- 5 micron PP sediment filter
- GAC coconut shell carbon filter
- 1 micron sediment PP filter
- 50 GPD RO membrane element
- Mineralization filter

SPECIFICATION:

Code	Flow capacity, LPD (GPD)	Inlet pressure, bar (psi)	Connections	Total volume of storage tank, L (gal)	Dimensions, H x W x D, mm (in)
MO550MPECOSTD	190 (50)	2–5 (29.0–72.5)	1/2", 3/8"	12 (3.2)	455 × 410 × 195 (17.9 x 16.1 x 7.7)

COMPONENTS:

- Filter housing with pump
- · Ecosoft pack of pre-filters for reverse osmosis filter
- Membrane element 50 GPD (190 LPD)
- Ecosoft mineralization filter
- Chrome ball valve faucet for purified water
- Plastic pressure tank (total vol. 12 L/3.2 gal, usable vol. up to 7 L/1.8 gal)
- and tank valve
- Feed water adapter, feed valve, drain saddle
- Pack of color tubes (4 pcs.) for convenient filter installation
- Service wrench
- User manual

Unit weight (net/gross), kg: 10.1/11.85 lb: 22.04/24.25 Box dimensions, m: 0.29 x 0.58 x 0.46 in: 11.4 x 22.83 x 18.11

ECOSOFT STANDARD REVERSE OSMOSIS FILTER WITH MINERALIZATION AND PUMP

Code	Product	Pieces in box	Boxes on pallet	Pieces on pallet
MO550MPECOSTD	Ecosoft Standard PRO reverse osmosis filter with mineralization and pump	1	24	24