

# GALACTIC MONOBLOCK

PRO RANGE OF FILTRATION UNITS



**Professional, versatile filtration** unit for in-ground and above-ground pools.


Includes a **filter** made of high-strength blown thermo-plastic, a 6-port **multiport valve** and a self-priming **pump**.

Wide **range of filtration rates**: flow rates from 5 m<sup>3</sup>/h to 14 m<sup>3</sup>/h.

Includes all accessories for **complete, quick installation**.

## CONDITIONS OF USE

|                              |                                        |
|------------------------------|----------------------------------------|
| Intended uses:               | Swimming pool and spa water filtration |
| Maximum water temperature:   | 35°C                                   |
| Normal operating pressure:   | 0.6-1.4 bar                            |
| Maximum pressure:            | 2.4 bar                                |
| Filter medium:               | Sand or glass                          |
| Filter medium particle size: | 0.4-0.8 mm                             |



Quick and easy installation.



Outstanding pro service.



Versatility: for installation in above-ground or in-ground pools.




# GALACTIC MONOBLOCK

PRO RANGE OF FILTRATION UNITS



Complies with Standard  
EN 16713-01



## Connections:

Connections included for  $\varnothing 38\text{mm}$  and  $\varnothing 50\text{mm}$  on filter and pump.



## Self-priming pump:

With built-in strainer and cable with plug for quick installation. Water bleeder included.



## Top valve:

6-port valve for filtration, backwashing, rinsing, recirculation, emptying and closing operations.



## Pressure gauge and air bleeder:

Pressure gauge and air bleeder included in the valve.



## Filter body:

Highly resistant filter body in anthracite gray and high-quality finishes. Easy top access via a locking band. Water bleeder included.



## Accessories:

All accessories are included for complete, quick installation: base, flexible hose and hardware.

\*Sand or glass filter medium not included

## TECHNICAL SPECIFICATIONS

| REF.  | FLOW RATE<br>m <sup>3</sup> /h | Ø FILTER<br>mm | PUMP POWER<br>HP | Ø CONNECTIONS<br>mm | SAND<br>kg* | DIMENSIONS (mm) |      |     |     |     | PACKAGING    |                  |
|-------|--------------------------------|----------------|------------------|---------------------|-------------|-----------------|------|-----|-----|-----|--------------|------------------|
|       |                                |                |                  |                     |             |                 |      |     |     |     | WEIGHT<br>Kg | DIMENSIONS<br>mm |
|       |                                |                |                  |                     |             | Ø               | A    | B   | C   | D   |              |                  |
| 74471 | 5                              | 380            | 1/3              | 38 / 50             | 40          | 380             | 860  | 710 | 635 | 295 | 20           | 790x600x700      |
| 74472 | 6                              | 400            | 1/3              | 38 / 50             | 40          | 400             | 905  | 710 | 650 | 295 | 20.5         |                  |
| 74473 | 8                              | 500            | 1/2              | 38 / 50             | 100         | 500             | 975  | 830 | 740 | 295 | 24           | 870x600x715      |
| 74474 | 10                             | 500            | 3/4              | 38 / 50             | 100         | 500             | 975  | 830 | 740 | 295 | 25.5         |                  |
| 74475 | 12                             | 600            | 3/4              | 38 / 50             | 150         | 600             | 1030 | 830 | 816 | 295 | 29           | 870x600x800      |
| 74476 | 14                             | 600            | 1                | 38 / 50             | 150         | 600             | 1030 | 830 | 816 | 295 | 30           |                  |

